

Design Criteria

- 1. Wind Speed (IRC) 90 mph three second gust (IBC) See Section 1603.1.4
- 2. Exposure assumed to be C unless location complies with definition
- 3. Ground snow load 30 psf
- 4. Roof snow load 30 psf
- 5. Footing depth minimum of 36 inches to bottom of footing
- Seismic Design Category B
- 7. Weathering Severe
- 8. Termite Slight to moderate
- 9. Winter design temperature 1°F
- 10. Ice barrier requirement not required
- 11. Air-Freezing index 1500
- 12. Mean annual temperature 45°F
- 13. Minimum plan size 22 x 34, Maximum plan size 30 x 36

Adopted Codes*

- 1. 2015 International Building Code
- 2. 2015 International Residential Code
- 3. 2015 International Plumbing Code
- 4. 2015 International Mechanical Code
- 5. 2015 International Fuel Gas Code
- 6. 2015 International Existing Building Code
- 7. 2015 International Energy Conservation Code
- 8. 2015 International Swimming Pool and Spa Code
- 9. 2015 International Fire Code
- 10.2014 National Electric Code
- 11. ICC A117.1-2009 Accessible and Usable Buildings and Facilities
- 12. ASME A17.1-2007 Safety Code for Elevators and Escalators

Building Inspection Division 9500 Civic Center Drive Thornton, CO 80229 303-538-7250

^{*} Current codes are effective September 6, 2016